



# MOTORS & BLOWERS

# **BROCHURE**

Y E A R 2 0 2 4

# TABLE OF CONTENT

C-FRAME MOTORS	PAGE 03
UNIT BEARING MOTORS	PAGE 03
3.3" SHADED POLE OR PSC MOTORS	PAGE 03
EC MOTORS	PAGE 04
5" MOTORS	PAGE 04
42/48/56 MOTORS	PAGE 04
AXIAL/COMPACT FANS	PAGE 05
BACKWARD CURVED MOTORS	PAGE 05
CENTRIFUGAL BLOWERS	PAGE 05
SQUIRELL CAGE BLOWERS	PAGE 06
HOT AIR BLOWERS	PAGE 06
TANGENTIAL (CROSS-FLOW) BLOWERS	PAGE 06
APPLICATIONS	PAGE 07

# DESIGN-IN ALTRAN PRODUCTS WITH CONFIDENCE

---

**01** **ISO9001:2016- Certification**  
International Standard for Quality  
Management System

**02** **ISO/TS16949:2015 Certification**  
International Standard for  
Automotive Device Manufacturing

**03** **ISO14000- Certification**  
International Standard for  
Environmental Compliance

**04** **RoHS Certificate of  
Compliance**  
Full RoHS-6 Compliance on Key  
Restricted Substances


**05** **Strict Control of Manufacturing  
Process**  
Measurement of Production Process  
with Lot Traceability

**06** **Continuous Improvement  
Philosophy**  
Ongoing Focus to Improve Products  
and Optimize Process

**07** **Most Models are UL and CE  
Approved**

# OUR MOTORS

---



## C-FRAME MOTORS

Voltages : 115V - 240V  
Gearbox option available  
1RPM - 3000RPM

---



## UNIT BEARING MOTORS

Voltages : 115V - 480V  
AC and EC options available  
7.5W- 45W

---



## 3.3" SHADED POLE OR PSC MOTORS

Voltages : 115V - 480V  
2 to 6 poles  
5W - 190W

---

# OUR MOTORS

---



## EC MOTORS

Voltages : 115V, 208-230V, 277V  
90W - 750W  
5 - 2200RPM

---



## 42/48/56 MOTORS

115V - 460V  
250W - 7500W  
Single/Dual shaft available  
Single Phase and 3-Phase

---



## 5" MOTORS

115-240V  
Shaded Pole and PSC options  
available  
Multi-speed option available

---

# OUR FANS

---



## AXIAL/COMPACT FANS

Ø0.8 in. to 33.4 in.

CFM: 0.8 to 7,800

5VDC - 48VDC

115VAC - 400VAC

---



## BACKWARD CURVED BLOWERS

24-48VDC

115V-230VAC

Ø5.2 in. to 24.8 in.

CFM: 150 to 13,000

---



## CENTRIFUGAL BLOWERS

Ø4.7 in. to 11 in.


CFM: 24 to 700

115VAC - 240VAC

---

# OUR FANS

---



## SQUIRELL CAGE BLOWERS

1.9 in. to 17.7 in.  
115VAC - 230VAC  
60 - 200 CFM  
Single and Dual options available

---



## CONVECTION FANS

Ø4 in. to 9 in.  
50 to 200 CFM  
115VAC - 240VAC

---



## TANGENTIAL (CROSS- FLOW) BLOWERS

4.7 in. to 24 in.  
50 to 250 CFM  
115VAC - 240VAC  
Single and Dual options available

---

# MOTORS AND BLOWERS APPLICATIONS

---

Electric heaters  
Humidifiers  
Range hoods  
Fireplace-blowers  
Pumps  
Air conditioners  
Walk-in refrigeration  
Commercial refrigeration  
Residential refrigeration  
Commercial and Industrial  
Ventilation  
Data Center Cooling  
Pool and Spa Pumps  
Home Ventilation  
Exhaust systems  
Convection ovens





“We Design.  
We Build.  
We Deliver.”



## Get In Touch

---

1741 Industrial Drive Sterling  
IL 61081

Tel: 815-632-3150

Fax: 815-632-3449

E: [sales@altranmagnetics.com](mailto:sales@altranmagnetics.com)

W: [www.altranmagnetics.com](http://www.altranmagnetics.com)